

Application No. 09/935,173

Kindly cancel claims 4-8.

4-8. canceled

NOT AVAILABLE COPY

9. (original) The stent assembly according to claim 1 wherein said trapping region is in an upstream portion of said downstream portion.

10. (original) The stent assembly according to claim 1 wherein said upstream portion comprises at least one of a meshwork and a plurality of coils.

Kindly amend claim 11 as follows:

11. (Amended) The stent assembly according to claim 10 wherein said at least one of a meshwork and coils has a coverage that varies along an axial portion of said stent assembly.

Kindly amend claim 12 as follows:

12. (Amended) The stent assembly according to claim 10 wherein said at least one of a meshwork and coils has a thickness that varies along an axial portion of said stent assembly.

Kindly amend claim 13 as follows:

13. (Amended) The stent assembly according to claim 10 wherein said at least one of a meshwork and coils is adapted to impart a radial force to a lumen in which said stent assembly is placeable, wherein said radial force varies along an axial portion of said stent assembly.

14. (original) The stent assembly according to claim 1 and further comprising a restrictor element disposed in at least one of said upstream and downstream portions, said restrictor element being adapted to limit expansion of said at least one of said upstream and downstream portions.

15. (original) The stent assembly according to claim 1 wherein at least one of said upstream and downstream portions comprises an anti-thrombogenic agent.

16. (original) The stent assembly according to claim 1 wherein at least one of said upstream and downstream portions comprises a thrombogenic agent.

17. (original) The stent assembly according to claim 1 wherein at least one of said upstream and downstream portions comprises a friction-enhancing material.

18. (original) The stent assembly according to claim 1 wherein at least one of said upstream and downstream portions comprises a friction-reducing material.

BEST AVAILABLE COPY

Application No. 09/935,173

91 19. (original) The stent assembly according to claim 3 wherein said upstream portion is placeable in a blood vessel upstream of a bifurcation in a blood vessel system, said bifurcation comprising a first downstream path and a second downstream path, said downstream portion being placeable in said second downstream path, and a space between said downstream portion and said upstream portion is alignable with said bifurcation, such that blood flows to both said first and second downstream paths with embolic material being trapped in said trapping region.

